

NPN POWER SILICON TRANSISTOR

Qualified per MIL-PRF-19500/454

Devices


2N5660 2N5661 2N5662 2N5663

Qualified Level

JAN, JANTX
JANTXV

MAXIMUM RATINGS

Ratings	Symbol	2N5660 2N5662	2N5661 2N5663	Unit
Collector-Emitter Voltage	V_{CEO}	200	300	Vdc
Collector-Base Voltage	V_{CBO}	250	400	Vdc
Collector-Emitter Voltage	V_{CER}	250	400	Vdc
Emitter-Base Voltage	V_{EBO}	6.0		Vdc
Base Current	I_B	0.5		Adc
Collector Current	I_C	2.0		Adc
		2N5660 2N5661	2N5662 2N5663	
Total Power Dissipation @ $T_A = +25^{\circ}C$ @ $T_C = +100^{\circ}C$	P_T	2.0 ⁽¹⁾	1.0 ⁽²⁾	W
		20 ⁽³⁾	15 ⁽⁴⁾	W
Operating & Storage Junction Temperature Range	T_J, T_{stg}	-65 to +200		$^{\circ}C$



TO-66*
(TO-213AA)
2N5660, 2N5661



TO-5*
2N5662, 2N5663

THERMAL CHARACTERISTICS

Characteristics	Symbol	2N5660 2N5661	2N5662 2N5663	Unit
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	5.0	6.67	$^{\circ}C/W$
Junction-to-Ambient	$R_{\theta JA}$	87.5	145.8	

- 1) Derate linearly 11.4 mW/ $^{\circ}C$ for $T_A > +25^{\circ}C$
- 2) Derate linearly 5.7 mW/ $^{\circ}C$ for $T_A > +25^{\circ}C$
- 3) Derate linearly 200 mW/ $^{\circ}C$ for $T_C > +100^{\circ}C$
- 4) Derate linearly 150 mW/ $^{\circ}C$ for $T_C > +100^{\circ}C$

*See appendix A for package outline

ELECTRICAL CHARACTERISTICS ($T_C = 25^{\circ}C$ unless otherwise noted)

Characteristics	Symbol	Min.	Max.	Unit
-----------------	--------	------	------	------

OFF CHARACTERISTICS

Collector-Emitter Breakdown Voltage $I_C = 10$ mAdc	2N5660, 2N5662 2N5661, 2N5663	$V_{(BR)CEO}$	200 300	Vdc
Collector-Base Breakdown Voltage $I_C = 10$ mAdc, $R_{BE} = 100\Omega$	2N5660, 2N5662 2N5661, 2N5663	$V_{(BR)CER}$	250 400	Vdc
Emitter-Base Breakdown Voltage $I_E = 10$ μ Adc		$V_{(BR)EBO}$	6.0	Vdc

ELECTRICAL CHARACTERISTICS (con't)

Characteristics	Symbol	Min.	Max.	Unit
Collector-Emitter Cutoff Current V _{CE} = 200 Vdc V _{CE} = 300 Vdc	I _{CES}		0.2	μAdc
2N5660, 2N5662 2N5661, 2N5663			0.2	μAdc
Collector-Base Cutoff Current V _{CB} = 200 Vdc V _{CB} = 250 Vdc V _{CB} = 300 Vdc V _{CB} = 400 Vdc	I _{CBO}		0.1	μAdc
2N5660, 2N5662			1.0	mAdc
2N5660, 2N5662			0.1	μAdc
2N5661, 2N5663 2N5661, 2N5663			1.0	mAdc

ON CHARACTERISTICS ⁽⁵⁾

Forward-Current Transfer Ratio I _C = 50 mAdc, V _{CE} = 2.0 Vdc I _C = 0.5 Adc, V _{CE} = 5.0 Vdc I _C = 1.0 Adc, V _{CE} = 5.0 Vdc I _C = 2.0 Adc, V _{CE} = 5.0 Vdc	h _{FE}	2N5660, 2N5662 2N5661, 2N5663	40 25		
2N5660, 2N5662 2N5661, 2N5663		40 25	120 75		
All Types		15			
All Types		5.0			
Collector-Emitter Saturation Voltage I _C = 1.0 Adc, I _B = 0.1 Adc I _C = 2.0 Adc, I _B = 0.4 Adc	V _{CE(sat)}		0.4 0.8		Vdc
Base-Emitter Saturation Voltage I _C = 1.0 Adc, I _B = 0.1 Adc I _C = 2.0 Adc, I _B = 0.4 Adc	V _{BE(sat)}		1.2 1.5		Vdc

DYNAMIC CHARACTERISTICS

Magnitude of Common Emitter Small-Signal Short-Circuit Forward Current Transfer Ratio I _C = 0.1 Adc, V _{CE} = 5.0 Vdc, f = 10 MHz	h _{fe}	2.0	7.0		
Output Capacitance V _{CB} = 10 Vdc, I _E = 0, 100 kHz ≤ f ≤ 1.0 MHz	C _{obo}		45		pF

SWITCHING CHARACTERISTICS

Turn-On Time V _{CC} = 100 Vdc; I _C = 0.5 Adc; I _{B1} = 15 Adc V _{CC} = 100 Vdc; I _C = 0.5 Adc; I _{B1} = 25 Adc	t _{on}	2N5660, 2N5662 2N5661, 2N5663	0.25 0.25		μs
Turn-Off Time V _{CC} = 100 Vdc; I _C = 0.5 Adc; I _{B1} = -I _{B2} = 15 Adc V _{CC} = 100 Vdc; I _C = 0.5 Adc; I _{B1} = -I _{B2} = 25 Adc		t _{off}	2N5660, 2N5662 2N5661, 2N5663	0.85 1.2	

SAFE OPERATING AREA

DC Tests T _C = +100°C, 1 Cycle, t ≥ 1.0 s					
Test 1 V _{CE} = 10 Vdc, I _C = 2.0 Adc V _{CE} = 7.5 Vdc, I _C = 2.0 Adc					
Test 2 V _{CE} = 40 Vdc, I _C = 500 mAdc V _{CE} = 25 Vdc, I _C = 600 mAdc					
Test 3 V _{CE} = 200 Vdc, I _C = 36 mAdc V _{CE} = 200 Vdc, I _C = 27 mAdc					
Test 4 V _{CE} = 300 Vdc, I _C = 19 mAdc V _{CE} = 300 Vdc, I _C = 14 mAdc					

(5) Pulse Test: Pulse Width = 300μs, Duty Cycle ≤ 2.0%.