

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 (818) 701-4939 Fax:

Features

- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information) For Surface Mount Application
- Low Forward Voltage and Extremely Low Thermal Resistance
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

Maximum Ratings

- Operating Temperature: -65°C to +125°C
- Storage Temperature: -65°C to +150°C
- Maximum Thermal Resistance: 305 °C/W Junction to Ambient


MCC Catalog Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
MBR0520L	SD	20V	14V	20V
MBR0530L	SE	30V	21V	30V
MBR0540L	SF	40V	28V	40V

Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	I_F	0.5A	
Peak Forward Surge Current	I _{FSM}	5.5A	8.3ms half sine
Maximum Forward voltage			
MBR0520L	V _F	0.3V	I _F =0.1A
WDI(0020E		0.385V	I _F =0.5A
MBR0530L		0.375V	I _F =0.1A
MBR00002		0.43V	I _F =0.5A
MBR0540L		0.51V	I _F =0.5A
MDI(00+0E		0.62V	I _F =1.0A
Maximum DC Reverse Current At Rated DC Blocking Voltage	I _R		
MBR0520L		75uA	V _R =10V
MDI(0020E		250uA	V _R =20V
MBR0530L		20uA	V _R =15V
MDI(0000E		130uA	V _R =30V
MBR0540L		10uA	V _R =20V
WDI\0040L		20uA	V _R =40V
Typical Junction Capacitance	CJ	170pF	V _R =0, f=1MHz
Power Dissipation	PD	410mW	

MBR0520L THRU **MBR0540L**

0.5 Amp **Schottky Rectifier** 20 to 40 Volts



DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
А	.140	.152	3.55	3.85	
В	.100	.112	2.55	2.85	
С	.055	.071	1.40	1.80	
D		.053		1.35	
Е	.012	.031	0.30	.78	
G	.006		0.15		
Н		.01		.25	
J		.006		.15	
	5		TED SOL LAYOUT 0.093" ——		

www.mccsemi.com

0.036"



MBR0520L thru MBR0540L




Figure 1. Typical Reverse Current of MBR0520L




Figure 2. Typical Reverse Current of MBR0530L




Figure 3. Typical Reverse Current of MBR0540L





Ordering Information :

Device	Packing	
Part Number-TP	Tape&Reel: 3Kpcs/Reel	

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

