

2SK1266

Silicon N-channel Power F-MOS FET

■ Features

- Low ON resistance $R_{DS(on)}$: $R_{DS(on)1} = 0.08\Omega$ (typ.)
- High switching rate : $t_f = 180\text{ns}$ (typ.)
- No secondary breakdown
- For low voltage driving ($V_{GS} = 4\text{V}$)


■ Application

- DC-DC converter
- No contact relay
- Solenoid drive
- Motor drive

■ Absolute Maximum Ratings ($T_c = 25^\circ\text{C}$)

Item	Symbol	Value	Unit
Drain-source voltage	V_{DSs}	150	V
Gate-source voltage	V_{GSs}	± 20	V
Drain current	DC	I_D	20
	Peak-to-peak value	I_{DP}	40
Power dissipation	$T_c = 25^\circ\text{C}$	P_D	45
	$T_a = 25^\circ\text{C}$		2.0
Channel temperature	T_{ch}	150	$^\circ\text{C}$
Storage temperature	T_{stg}	$-55 \sim +150$	$^\circ\text{C}$

■ Package Dimensions



■ Electrical Characteristics ($T_c = 25^\circ\text{C}$)

Item	Symbol	Condition	min.	typ.	max.	Unit
Drain current	I_{DS}	$V_{DS} = 130\text{V}$, $V_{GS} = 0$			10	μA
Gate-source current	I_{GS}	$V_{GS} = \pm 20\text{V}$, $V_{DS} = 0$			± 1	μA
Drain-source voltage	V_{DS}	$I_D = 1\text{mA}$, $V_{GS} = 0$	150			V
Gate threshold voltage	V_{th}	$V_{DS} = 10\text{V}$, $I_D = 1\text{mA}$	1		2.5	V
Drain-source ON resistance	$R_{DS(on)1}$	$V_{GS} = 10\text{V}$, $I_D = 10\text{A}$		0.08	0.12	Ω
Drain-source ON resistance	$R_{DS(on)2}$	$V_{GS} = 4\text{V}$, $I_D = 10\text{A}$		0.09	0.135	Ω
Forward transfer admittance	$ Y_{fs} $	$V_{DS} = 10\text{V}$, $I_D = 10\text{A}$	10	20		S
Input capacitance	C_{iss}	$V_{DS} = 10\text{V}$, $V_{GS} = 0$, $f = 1\text{MHz}$		3450		pF
Output capacitance	C_{oss}				600	pF
Reverse transfer capacitance	C_{rss}				150	pF
Turn-on time	t_{on}	$V_{GS} = 10\text{V}$, $I_D = 10\text{A}$		90		ns
Fall time	t_f				180	ns
Delay time	$t_d(\text{off})$	$V_{DD} = 100\text{V}$, $R_L = 10\Omega$		770		ns

■ 6932852 0017165 0T2 ■

—1167—

Panasonic

